



Basic Impregnator™

TECHNICAL DATA SHEET

PRODUCT BENEFITS

EcoStone Solutions Basic Impregnator is an impregnating, natural look, water based stain protection formula for all stones. Effective for showers, grout, and outdoor areas. Allows vapor transmission.

RECOMMENDED SURFACES

For use on:

- Travertine
- Granite
- Marble
- Limestone
- Clay Products
- Slate
- Grout
- Sandstone

Available Sizes

Quarts, Gallons, 5 gallon pails, 55 gallon drums

Coverage

200-1000 SF (20-94 Sq meters) per coat per gallon depending on the porosity and texture of the material, method of application, humidity, and surface temperature.

Directions

- Always test in an inconspicuous area before general use & refer to product label for complete information.
- Make sure surface is clean, vacuuming or sweeping off all debris.
- Mask off and protect areas such as baseboards or adjacent surfaces not intended for treatment.
- Make sure surface is clean and dry prior to application.
- EcoStone Solutions Basic Impregnator may be applied to damp surfaces 4 hours after moisture has been removed.
- Apply an even coat using a paint pad, paint brush, paint roller, or low-pressure sprayer delivering a coarse wet spray.
- Allow penetration for 10-15 minutes, then wipe off all remaining product immediately.
- A full cure can be expected in 48-72 hours. Foot traffic can begin after 4 hours.
- Reapply Basic Impregnator as needed for periodic maintenance this will depend on traffic patterns, sun exposure, maintenance procedures, etc. Test before usage to prevent residue formation.

- No chlorinated solvents
- No petroleum distillates
- VOC compliant in all states
- Environmentally responsible
- Easy to use and low odor

- Excellent protection against the toughest oil and water-based stains
- This product may help you achieve LEED certification



For more information on this product and other products for tile and stone care please visit your distributor or our website at www.ecostonesolutions.com